


PRODUCT SPECIFICATION					DATE: 04/12/15
PRODUCTNAME: COMMERCIAL : Turbo Rafou PRODUCTION : Turbo plat res AF + foulard CODE : 02168...001047					 EN 14041  
COLOURS/FARBEN 1046 - 1081 - 2071 - 2101 - 2122 - 3063 - 3090 - 4045 COLORIS/KLEUREN: 5059 - 5088 - 5101 - 6085 - 6888 - 7021 - 7075 - 7745					
WIDTH/BREITE/LARGEUR/BREEDTE: 2 m 4 m LENGTH/LÄNGE/LONGUEUR/LENGTE: 30 m 30 m					EN 1307
REMARKS/BEMERKUNGEN/REMARQUES/OPMERKINGEN: minimum order quantity = 1 standard unit Suitable for underfloor heating - Thermal resistance ISO 8302: 0,086 m²/K/W - Acoustical impact noise reduction: 20 dB - AbZ number: Z-156.601-1418 - GUT ID number : 123183 - Prodis ID number: 6B5FCB75					
TECHN. INFORM.	TECHN. DATEN	CAR. TECHN.	TECHN. GEGEV.	NORM	
MANUFACTURING PROCESS	HERSTELLUNGS-ART	TECHN. DE FABRICATION	FABRICATION-METHODE	DIN61151	needle-felt
SURFACE ASPECT	OBERFLÄCHEN-STRUKT.	ASPECT DU SURFACE	POOL-STRUCTUUR		flat
PILE COMPOSITION	POL MATERIAL	COMP. DU POIL	POOL-MATERIAAL		100% Polyprop.
PILE WEIGHT	POLGEWICHT	POIDS DU POIL	POOLGEWICHT	ISO8543	900gr/m² ± 10%
PILE HEIGHT	POLHÖHE	HAUT. DU POIL	POOLHOOGTE		0mm ± 10%
PRIM. BACKING	PRIM. RÜCKEN-AUSSTATTUNG	DOSSIER PRIM.	PRIM. BACKING	ISO2424	Carboxylated styrene butadiene latex
SEC. BACKING	SEC. RÜCKEN-AUSSTATTUNG	DOSSIER SEC.	SEC. BACKING	ISO2424	
BACKING WEIGHT	RÜCKEN-GEWICHT	POIDS DU SUPPORT	BACKING-GEWICHT		170gr/m² ± 10%
TOTAL WEIGHT	GESAMTGEWICHT	POIDS TOTAL	TOTAALGEWICHT	ISO8543	1070gr/m² ± 10%
TOTAL HEIGHT	GESAMTHÖHE	HAUTEUR TOT.	TOT. HOOGTE	ISO1765	5mm ± 10%
TECHN. INFORM.	TECHN. DATEN	CAR. TECHN.	TECHN. GEGEV.	NORM	
PERMANENT ANTISTATIC	PERMANENT ANTISTATISCH	ANTISTATIQUE PERMANENT	PERMANENT ANTISTATISCH	ISO6356	< 2.0 kV
TO/RUBBING	REIBECHTHEIT	AU FROTTEM.	WRIJFECHTH.	ISO105X12	5
CLASSIFICATION	KLASSIFIKATION	CLASSIFICATION	CLASSIFICATIE	En 1307	Heavy Commercial 33 Lc1
FLAMMABILITY	BRAND-VERHALTEN	COMPOTEMENT AU FEU	BRANDGEDRAG	EN 13501-1	Cfl S1 Fully Adhesive
USAGE	ANWENDUNG	EMPLOI	GEBRUIK		Contract
Due to limitations of the manufactu- ring process, colour may slightly vary from batch to batch. We reserve the right to alter technical specifications.		Durch dem Produktions Prozess bedingt, können geringe Farbabweichungen von Partie zu Partie auftreten. Wir behalten uns das Recht um die Technischen Daten zu ändern.		Du à des limitations de production, le coloris peut varier légèrement d'une production à l'autre. Le fabrication se réserve le droit de modifier les caractéristiques techniques.	
				Door beperkingen in het productieproces, zijn geringe kleurafwijkingen van partij tot partij mogelijk. Wij behouden het recht de technische gegevens aan te passen.	